

前瞻

ADVANCED

創新

INNOVATION

人性化

USERS FRIENDLY



液態瓦斯 安全附屬設備

SAFETY ACCESSORY
EQUIPMENT FOR LPG

志豪工業有限公司
ZU HOW INDUSTRY CO., LTD.

瓦斯氣化器

GAS VAPORIZER

瓦斯強制氣化器的功用，能將液化瓦斯穩定的輸出，並使瓦斯桶內的瓦斯能完全耗盡。使用強制氣化器能使瓦斯供氣壓力穩定，不因瓦斯大量輸出導致瓦斯壓力下降而受到影響。

The function of gas vaporizer is to be output of LPG stable and make the gas exhaust completely. Using gas vaporizer can stabilize the gas supply pressure without being affected by the decrease in gas pressure due to a large amount of gas output.



使用優點 ADVANTAGE



防止鋼瓶結霜 PREVENT FROSTING of CYLINDERS

防止液態瓦斯殘留 PREVENT RESIDUAL LPG

供氣壓力穩定 STABILIZE THE SUPPLY PRESSURE

空燃比穩定提升效率 STABILIZE AIR-FUEL RATIO TO IMPROVE EFFICIENCY

燃燒穩定 STABILIZE COMBUSTION

產品特點 PRODUCT FEATURE



堅固耐用
Stable & Durable

全不銹鋼內膽，不易鏽蝕、脆化；
結構穩定，堅固耐用。

All stainless steel liner.
Not easy to rust and embrittlement.
Stable structure and using durable.



自動恆溫
Automatic Thermostat

水溫由溫控控制在55°C~80°C，設有
防超溫裝置，防止溫度過高。

The water temperature is controlled at
55°C ~ 80°C by thermostat, due to
anti-over temperature device to prevent
over temperature.



防爆裝置
Explosion Proof Device

電控箱及加熱器採防爆設計，安全
性提升。

The control panel and heater assemble
explosion proof device to improve
safety.



警示系統
Warning System

設有低水位警示及超溫警示，預防加
熱器乾燒、水溫過高。

With low water level and over temperature
warning to prevent the heater idle burning
and water temperature too high.



超量限制
Over Limit

內部特殊設計，可防止超量使用。

Internal special designed to prevent
excessive using.



安全裝置
Safety Device

安全洩壓閥可將超壓氣體自動排出，
超溫自動洩放；液態瓦斯阻斷裝置可
防止液體經管道滲出。

The safety relief valve can discharge
the overpressure gas and over
temperature gas automatically. The LPG
arrester device can prevent liquid
seeping from the pipeline.

瓦斯氣化器標準規格 GAS VAPORIZER STANDARD SPECIFICATIONS

型式 Model			VG-30	VG-60	VG-100	VG-120	VG-200	VG-240
設計壓力 Design pressure		kgf/cm ²	18					
耐壓試驗壓力 Pressure proof testing		kgf/cm ²	27					
設計溫度 Design temperature		°C	85					
使用溫度 Using temperature		°C	55~80					
氣化能力 Vaporization of capability		kg/hr	30	60	100	120	200	240
電熱器 Heater		KW	5*1	9*1	15*1	18*1	15*2	18*2
電流 Voltage	3ψ220V	A	13.1	23.6	39.4	47.2	78.7	94.5
	3ψ380V		7.6	13.7	22.8	27.3	45.6	54.7
注水量 Water injection rate		L	28	52	76	80	120	125
液體入口 Inlet of liquid		A	15	15	25	25	25	25
氣體出口 Outlet of gas		A	15	25	40	40	40	40



備註：

1.LPG氣體使用量不能大於氣化器的氣化量


The amount of LPG gas is unable to be more than vaporization of the vaporizer.

2.只限於使用LPG氣體(液化石油氣),不適用其他任何氣體

Only using LPG, not applicable to any other gas.

3.電源電壓請在額定±10%範圍內使用

Using the power of supply voltage within the rated range of ±10%.



液體管路	Liquid Pipeline	球閥	Ball Valve
氣體管路	Gas Pipeline	逆止閥	Check Valve
電器管路	Electric wire pipeline	高壓瓦斯管	Gas Hose
Gas pipe line	Gas pipe line	自動緊急遮斷裝置	Emergency Shut-Off Valve
Gas vaporizer	Gas Vaporizer	自動切替器	Automatic Changeover Switch
Inlet of Liquid	Inlet of Liquid	中壓減壓閥	Medium Pressure Reducing Valve
Outlet of Gas	Outlet of Gas	低壓減壓閥	Low Pressure Reducing Valve
Safety valve	Safety Valve	微壓錶	Micro Pressure Gauge
Drain valve	Drain Valve	法蘭口	Flange
Control Panel	Control Panel	Y型過濾器	Y-Strainer
Water outlet	Water outlet	安全閥	Safety Valve
Gas detector controller wire	Gas detector controller wire		

瓦斯氣化器標示圖

DISPLAY OF GAS VAPORIZER



液態瓦斯阻斷器&油氣分離器

LPG ARRESTER & OIL-GAS SEPARATOR

專為管路加裝設計，安全可靠。可防止液態經管道滲出，流至燃燒系統造成氣爆的危險。

此裝置兼具油氣分離的功能，能夠防止瓦斯油流出至閥門，避免造成管路阻塞或動作異常。

The function is specially designed for pipeline installation. It would be able to prevent the liquid seeping out from the pipeline and flowing into the combustion system cause of the gas explosion.

It is not only with oil & gas separation, but also prevents gas oil flowing into valve to avoid pipe blockage or operation abnormal.



瓦斯洩漏遮斷操作系統

GAS LEAKAGE SHUTTING OPERATING SYSTEM



瓦斯洩漏遮斷操作系統能同時裝設瓦斯、一氧化碳、地震、煙霧感知器，並具備遠端監控及語音發報功能。瓦斯遮斷閥具遠端遮斷功能，能同時偵測瓦斯或因瓦斯不完全燃燒引起的一氧化碳警報，自動將瓦斯遮斷，避免危險。

The gas leakage shutting operating system not only equip with gas, carbon monoxide, earthquake, and smoke detector at the same time, but also have remote monitoring and voice reporting of function.

The gas shutoff valve has a remote shutting off function. It will detect gas or gas combustion incomplete to affect CO detector, and then shut off gas to avoid any damage.



地震感知器
Earthquake Sensor



一氧化碳感知器
CO Detector



異常警報蜂鳴指示燈
Strobe Siren



瓦斯漏氣感知器
Gas Leak Detector



遠端遮斷開關
Network Control
Breaking Switch



煙霧感知器
Smoke Detector



液態瓦斯遮斷閥
Normally Open Manual
Reset Solenoid Valve



服務團隊

SERVICE TEAM

本公司是專業的鍋爐製造廠，如有任何需求歡迎與我們聯絡。

ZU HOW INDUSTRY IS A PROFESSIONAL BOILER MANUFACTURER.
PLEASE DO NOT HESITATE TO CONTACT US WITH ANY INQUIRY.

雲林總公司 YUNLIN HEAD OFFICE

雲林縣虎尾鎮頂溪里崁腳30號

No.30 Kanjiao, Dingxi Village, Huwei Township, Yunlin County, 63250 Taiwan.

+886-5-622-3611 zuhow@ms32.hinet.net

+886-5-622-3077 www.zuhow.com.tw
www.zuhow-boiler.com

台北分公司 TAIPEI BRANCH

新北市土城區 Tucheng District, New Taipei City

+886-2-2268-6566
 +886-2-2269-3339

台中分公司 TAICHUNG BRANCH

台中市霧峰區 Wufeng District, Taichung City

+886-4-2332-3111
 +886-4-2331-1122

台南分公司 TAINAN BRANCH

臺南市新化區 Xinhua District, Tainan City

+886-6-598-4525
 +886-6-598-2425

台東分公司 TAITUNG BRANCH

台東縣台東市 Taitung City, Taitung County

+886-89-385-168
 +886-89-385-169

河內分公司 HANOI BRANCH

河內市福壽縣 Fushou County, Hanoi City

+84-9381-44717
 +84-2432-047566

苗栗分公司 MIAOLI BRANCH

苗栗縣頭份市 Toufen City, Miaoli County

+886-37-676-123
 +886-37-676-790

嘉義分公司 CHIAYI BRANCH

嘉義縣中埔鄉 Zhongpu Township, Chiayi County

+886-5-239-1515
 +886-5-230-7575

高雄分公司 KAOHSIUNG BRANCH

高雄市仁武區 Renwu District, Kaohsiung City

+886-7-375-3111
 +886-7-373-9796

泰國工廠 THAILAND FACTORY

泰國羅勇 Rayong, Thailand

+66-3-865-0598~600
 +66-3-865-0596~597

越南工廠 VIETNAM FACTORY

胡志明市 Ho Chi Minh City, Vietnam

+84-8-3796-8078~9
 +84-8-3796-8077

發行日期 Date of issue : 2021/09

本公司保留一切更改權利，恕不另行通知。
We reserve all the right to change, without notice.

內容資料及圖片嚴禁轉載。
Reproduction of all contents and images are strictly prohibited.